



PRODUCT NAME : MFCARB WT B1240
 PRODUCT TYPE : Normal Grade
 APPLICATION : Water Treatment
 ACTIVATION AGENT : STEAM/AIR
 MESH SIZE : 12X40 USS MESH

Parameter	Unit	Spec.	Test Method
Moisture	%	5%	ASTM D2867
Bulk density	Kg/m ³	500 min	ASTM D2854
Ash Content	%	5%	ASTM D2866
pH		9-11	ASTM D3838
CTC	%	45 min	ASTM D3467
Iodine Number	mg/g	900 min	ASTM D4607
Ball Pan Hardness	No	97%	ASTM D3802
BET – Surface Area	m ² /gm	950 min	BET-m2

Particle Size Distribution			
+12 USS MESH	%	5 max	ASTM D2862
-40 USS MESH	%	5 max	ASTM D2862

PACKING The material is packaged in 500kgs net in poly woven bags or 25kgs net in PP bags with inner lining will be shrink wrapped and palletized in to fumigated Pallets as per ISPM 15 standard.

STORAGE: Store the material in a cool dry area, away from sun light. **SHELFLIFE:** More than 5Years when keeping in proper packed condition

LABELING: The label displays the product name, lot number, net weight, gross weight, manufacturer name& address and other information or marks as required by the customer.

