



TRADE NAME : MFCARB WT B830
 APPLICATION : WATER TREATMENT
 SOURCE : COCONUT
 ACTIVATION AGENT : STEAM/AIR
 MESH SIZE : 8 X30 USS MESH

PARAMETER	UNIT	SPEC.	TEST METHOD
Apparent density	Kg/m ³	520 min.	ASTM D2854
Iodine Number	mg/gm	900 min.	ASTM D4607
Ash Content	Wt. %	5 max.	ASTM D2866
CTC Adsorption	%	45min	ASTM D3467
Moisture	Wt. %	5 max.	ASTM D2867
pH	-	9-11	ASTM D3838
Hardness	%	98	ASTM D3802

Particle Size Distribution			
+8 USS MESH	Wt %	5 max.	ASTM D2862
-30 USS MESH	Wt %	4 max.	ASTM D2862

PACKING The material is packaged in 500kgs/550 Kgs net in poly woven bags or 25kgs net in PP bags with inner lining will be shrink wrapped and palletized in to fumigated Pallets as per ISPM 15 standard.

STORAGE: Store the material in a cool dry area, away from sunlight. **SHELF LIFE:** More than 5 Years when keeping in proper packed condition

LABELING: The label displays the product name, lot number, net weight, gross weight, manufacturer name & address and other information or marks as required by the customer

